

rated power 3 kW  
 rated voltage 24 V  
 rated current 17.6 A  
 rated speed 2600 min<sup>-1</sup>  
 operation mode S2-9min  
 excitation compound  
 protection IP 21  
 insulation F  
 weight 11.34 kg  
 length 224  
 char. curve C24B13  
 rotation C.W./D.E  
 conn. diag. fig. 1

EC 3/2,4/26-01  
 0 31 12 6010

ECH 1/7,2/19-01  
 0 19 41 9010

rated power 1 kW  
 rated voltage 72 V  
 rated current 19 A  
 rated speed 1900 min<sup>-1</sup>  
 operation mode S1  
 excitation chunt  
 protection IP 21  
 insulation F  
 weight 10.33 kg  
 length 224  
 char. curve H72B02  
 rotation C.W./D.E  
 conn. diag. fig. 2





fig. 1

fig. 2

DC motor EC 3/2,4/26-01  
 IP [E] excitation [E] comp  
 insulation class [E] min<sup>-1</sup> 2600  
 kW [3] V [24] A [17.6]  
 kg [11.34] duty cycle [S2-9 min]

DC motor ECH 1/7,2/19-01  
 IP [E] excitation [E] chunt  
 insulation class [E] min<sup>-1</sup> 1900  
 kW [1] V [72] A [19]  
 kg [10.33] duty cycle [S1]

04.01.2007	
06.11.2006	
13.01.2005	
Rev.	Eiprom-EMS