


rated power
rated voltage
rated current
rated speed
operation mode
excitation
protection
insulation
weight
length L
char. curve
rotation

FC 5,2/4,5/28 FC 6/4,5/28 FC 5,2/2,2/28
0 36 32 8000 0 37 32 8000 0 36 12 8000

5,2 kW	6 kW	5,2 kW
48 V	48 V	24 V
145 A	170 A	295 A
2800 min ⁻¹	2800 min ⁻¹	2800 min ⁻¹
S4-2S7--240 c/h	S4-2S7--240 c/h	S4-2S7--240 c/h
Compound	Compound	Compound
IP 21	IP 21	IP 21
F	F	F
28 kg	28 kg	29,5 kg

C48E05 C48E03 C24E01



By an order specify the angle α .
Possible values are from 0° to 315° with a step of 45° by rotation of the front end bell.

KOSTOV MOTORS		excit. <input type="checkbox"/>		insulation <input type="checkbox"/>	
kW <input type="text"/>	A <input type="text"/>	V <input type="text"/>	body <input type="checkbox"/>		
rpm <input type="text"/>	kg <input type="text"/>	S.N. <input type="text"/>			
www.kostov...moldova.com					

16.11.2006	Balkanear "G. Kostov" JSC
24.10.1997	
10.03.1997	
21.11.1995	
Rev.	