



EC 3/1,2/35-15 EC 3/2,4/35-15 EC 3/4,8/35-15 EC 1/7,2/35-15 EC 3/2,4/35-15.2
 0 31 03 5150 0 31 13 5150 0 31 33 5150 0 19 43 5150 0 31 13 5152

rated power	3 kW
rated voltage	12 V
rated current	360 A
rated speed	3500 min ⁻¹
operation mode	S2-6min
excitation	Compound
protection	IP 20
insulation	F
weight	9,92 kg
length L	232
char. curve	C24B05
rotation	C.W./D.E

3 kW	24 V	168 A	3500 min ⁻¹	S2-10min	Compound	IP 20	F	9,5 kg	212	C.W./D.E
48 V	84 A	3500 min ⁻¹	S2-7min	Compound	IP 20	F	9,6 kg	212	C.W./D.E	

1 kW	72 V	21,5 A	3500 min ⁻¹	S2-10min	Compound	IP 20	F	9,5 kg	212	C.W./D.E
3 kW	24 V	168 A	3500 min ⁻¹	S2-10min	Compound	IP 20	F	9,5 kg	212	C.W./D.E



26.04.2007	12.01.2001	09.10.1998	20.10.1997
02.11.2006	05.08.2005		
26.04.2007	02.11.2006	05.08.2005	12.01.2001
09.10.1998	20.10.1997		

Elprom-EMS

Rev.	
------	--