


Torque
10+2 Nm
13

SPLINE DETAIL

- 19 Teeth equally spaced
- 24/48 Pitch
- .9449/.1.8898 Wide
- .772/.767 Inside diameter
- .859/.850 Outside
- 45° Pressure angle

ETH 8,6/4,8/38
0 41 33 8000

- rated power 8,6kW
- rated voltage 48 V
- rated current 230A
- rated speed 3800 min⁻¹
- operation mode S2-60 min
- excitation indep.
- protection IP 21
- insulation F
- weight 38 kg
- char. curve



NB: 1. Coating RAL 9011 (black)

Rotation (viewed from drive end)
CCW: F1 → ⊕; F2 → ⊖; | A1 → ⊕; A2 → ⊖;
CW: F1 → ⊖; F2 → ⊕; | A1 → ⊕; A2 → ⊖;

SEE MOTORS	ETH 8,6/4,8/38
excit. INDP	INSULATOR F
IP 21	IP 21
excit. S2-60min	excit. S2-60min
rated power 8,6 kW	rated voltage 48 V
rated current 230 A	rated speed 3800 min ⁻¹
operation mode S2-60min	excitation indep.
protection IP 21	insulation F
weight 38 kg	

www.kostov-motors.com

24.11.2009	Balkancar "G. Kostov" JSC
07.08.2008	
11.07.2008	
Rev.	